

Steering

| | |
|-------------------------------------------|-----------------|
| Type | Rack and pinion |
| Turning circle | 7.32m (24ft) |
| Castor | 12° |
| Camber | 1° positive |
| Toe-in | Zero |
| King pin inclination | 9° |
| Conforming to European Safety Regulations | |

Chassis data

| | |
|--------------------------|----------------------------------------------------------------------------------|
| Type | Box section with tubular cross-members and channel section diagonal cross-braces |
| Wheel base | 2146 mm (84.5 in) |
| Track—front and rear | 1244.6 mm (49.0 in) |
| Ground clearance (laden) | 127.0 mm (5 in) |

Wheels and tyres

| | |
|-------------|------------------|
| Road wheels | 350B × 10 |
| Tyres | 145 × 10 radials |

Capacities

| | |
|----------------------------------|---------------------------|
| Engine including filter | 3.13 litres (5.50 pints) |
| Gearbox | 0.64 litres (1.125 pints) |
| Rear axle | 1.28 litres (2.25 pints) |
| Steering rack and pinion | 0.19 litres (0.33 pints) |
| Cooling system, including heater | 3.69 litres (6.5 pints) |
| Fuel tank | 27.30 litres (6 gallons) |

Vehicle dimensions

| | Saloon | Estate |
|------------------------------------|----------------------------|------------------------|
| Overall length | 3327.4 mm (131.0 in) | 3346.5 mm (131.75 in) |
| Overall width | 1422.4 mm (56.0 in) | 1422.4 mm (56.0 in) |
| Overall height | 1397.0 mm (55.0 in) | 1397.0 mm (55.0 in) |
| Loading height | 1016.0 mm (40.0 in) | 508.0 mm (20.0 in) |
| | (ground to tailgate sill) | (ground to rear floor) |
| Load width—Maximum | 1028.7 mm (40.5 in) | 850.9 mm (33.5 in) |
| | (width at tailgate sill) | (rear door aperture) |
| Load height—Maximum aperture | 457.2 mm (19.0 in) | 749.3 mm (29.5 in) |
| | (tailgate aperture height) | (rear door aperture) |
| Load height—Maximum inside vehicle | 850.9 mm (33.5 in) | 876.3 mm (34.5 in) |
| Length behind rear seat | 647.7 mm (25.5 in) | 693.1 mm (26.5 in) |
| Length with rear seat folded | 1092.2 mm (43.0 in) | 1168.4 mm (46.0 in) |
| Load floor width behind rear seat | 952.5 mm (37.5 in) | 952.5 mm (37.5 in) |

Load capacities

| | |
|------------------------------------------------------------------------------------------------------|---------------------------------|
| Saloon—capacity of boot area, rear seat up, spare wheel in position below tonneau cover | 0.230 mm (8.5ft ³) |
| Saloon—capacity of rear compartment with rear seat folded, spare wheel in position, up to roof level | 0.849 mm (30.0ft ³) |
| Estate—capacity of rear compartment, with spare wheel in position and rear seat up | 0.270 mm (9.5ft ³) |
| Estate—capacity of complete rear compartment, with spare wheel in position and rear seat folded | 1.132 mm (40.0ft ³) |

Kerb weight

| | |
|--------|---------------------|
| Saloon | 505.81 kg (1114 lb) |
| Estate | 538.9 kg (1187 lb) |

Maximum vehicle weights

| | |
|---------------------------------------|--------------------|
| Gross laden vehicle weight | 862.0 kg (1900 lb) |
| Approximate maximum pay load | 320 kg (700 lb) |
| Maximum recommended front axle weight | 363 kg (800 lb) |
| Maximum recommended rear axle weight | 550 kg (1210 lb) |
| Recommended towing weight (maximum) | 406 kg (896 lb) |